REMARKS

35 U.S.C. § 103 Rejections

The Examiner has rejected claims 7-9 under 35 U.S.C. § 103(a) as being unpatentable over <u>Hiyoshi</u> in view of <u>Owens</u> and further in view of <u>Ommen</u>.

Claim 7 includes a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader.

Specifically, claim 1 includes the limitation "a package substrate having top and bottom buildup layers, including a plurality of conductive traces and vias formed therein interconnecting top and bottom surfaces of the package substrate, disposed on a thermally conductive thermal substrate core, wherein a portion of the substrate core is exposed at a top surface of the package substrate for attachment of a heat spreader."

<u>Hiyoshi</u> does not teach or suggest a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader. <u>Hiyoshi</u> discloses a semiconductor device having semiconductor chips 351-354 mounted on a ceramic substrate 31 with a circular flange 32 around a periphery of the substrate 31 (Col. 6, lines 48-55). Copper plates 331 and 332 are bonded to the top and bottom surfaces of the ceramic substrate 31 (Col. 6, lines 61-

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806

Examiner: Vu, Quang D. Art Unit: 2811 63). The copper plates 331 and 332 are made of a homogenous material and do not include conductive traces or vias. Hiyoshi thus does not disclose buildup layers. Furthermore, as shown in Figure 2D, gate probe pins 471 and 472, along with conductive pillars 40, 41, and 45, extend away from the semiconductor chips 351-354 in a direction opposite the position of the copper plate 351 and do not interconnect top and bottom surfaces of the substrate on which the semiconductor chips 351-354 rest. Therefore, Hiyoshi not only fails to disclose buildup layers, but actually teaches away from having buildup layers on the package substrate that include vias that extend therethrough. Specifically, Hiyoshi does not teach or suggest a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader.

Owens does not teach or suggest a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader. Owens teaches a system for extending the life span of electronic components in a high-temperature well (Abstract). A thermal electric cooler 10 is attached to a well tool 12 and located proximate to an electronic component 20 within the well tool 12 (Col. 3, lines 60-67). As shown in Figure 3, a cold surface 30 of the thermal electric cooler 10 is positioned proximate to the electronic component 20

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806

so that the cooling effect of cold surface 30 withdraws thermal energy from the electronic component 20 (Col. 4, lines 48-51). A hot surface 32 of the thermal electric cooler 10 is in contact with tool 12 so that tool 12 acts as a heat sink to dissipate thermal energy away from thermal electric cooler 10 (Col. 4, lines 51-53). Owens makes no mention of package substrates or buildup layers. Specifically, Owens does not teach or suggest a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader.

Ommen does not teach or suggest a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader. Ommen teaches a package capable of spreading heat from a semiconductor die (Abstract). As illustrated in Figure 1, pad array carrier package 10 is a semiconductor package, which comprises a heat spreader 11 having a first major surface 12 and a second major surface 13 (Col. 2, lines 33-37). Heat spreader 11 has a plurality of apertures or holes 16 extending therethrough and is coated with an electrically non-conductive adhesive material 17 which fills holes 16 (Col. 2, line 59 through Col. 3 line 7). The adhesive material 17 coats the first and second major surfaces 12 and 13 (Col. 3, lines 12-13). An insulator layer 18 is formed on the adhesive material 17 and may cover the adhesive material 17 on both sides of the

Inventor(s): Timothy M. Takeuchi Examiner: Vu, Quang D. Application No.: 10/038,806 Art Unit: 2811 heat spreader 11 (Col. 3, lines 20-24). Top side conductive traces 20, bottom side conductive traces 24, and conductive pads 21 are formed on the insulator layer 18 (Col. 3, lines 51-55). A solder mask 26 is patterned over conductive traces 20 and 24 and over conductive pads 21 (Col. 4, lines 63-64). A protective metal cap 30 is bonded to the solder mask 26 using an adhesive material 27 (Col. 5, lines 7-8). The metal cap 30 serves as a heat spreader by promoting thermal conduction away from the semiconductor die 25 (Col. 5, lines 30-32). As clearly shown in Figure 1 the metal cap 30 is attached to the conductive traces 20 and 24 and conductive pads 21. Ommen thus teaches conductive traces in pads disposed on a substrate core with a heat spreader attached to the conductive traces and pads. Specifically, Ommen does not teach or suggest a package substrate having top and bottom buildup layers, with conductive traces and vias connecting a top surface to a bottom surface of the package substrate, disposed on a thermally conductive substrate core which has an exposed portion at a top surface thereof for attachment of a heat spreader.

Therefore, claim 7 is patentable over <u>Hiyoshi</u> in view of <u>Owens</u> and further in view of <u>Ommen</u> because claim 7 includes a limitation that is not taught or suggested by <u>Hiyoshi</u>, <u>Owens</u>, and <u>Ommen</u>.

Claims 8 and 9 are dependent on claim 7 and should be allowable for the same reasons as claim 7.

Applicant, accordingly, respectfully requests withdrawal of the rejections of claims 7-9 under 35 U.S.C. § 103(a) as being unpatentable over <u>Hiyoshi</u> in view of <u>Owens</u> and further in view of <u>Ommen</u>.

Inventor(s): Timothy M. Takeuchi
Application No.: 10/038,806

Examiner: Vu, Quang D.

Art Unit: 2811

The Examiner has rejected claims 10-15 and 18-20 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> in view of <u>Hiyoshi</u>.

Claim 10 includes a package substrate having a thermally conductive substrate core and a buildup layer being, having conductive traces and vias interconnecting top and bottom surface of the buildup layer, disposed only on a first portion of the substrate core and a heat spreader mounted to a second portion of a substrate core. Specifically, claim 10 includes the limitations "a package substrate including a thermally conductive core, having first and second portions, and a buildup layer, including a plurality of conductive traces and vias formed therein interconnecting top and bottom surfaces of the buildup layer, being disposed on only the first portion of the substrate core" and "a heat spreader mounted to the second portion of the substrate core."

<u>Lischner</u> and <u>Hiyoshi</u> do not teach or suggest a package substrate having a thermally conductive substrate core and a buildup layer being, having conductive traces and vias interconnecting top and bottom surface of the buildup layer, disposed only on a first portion of the substrate core and a heat spreader mounted to a second portion of a substrate core.

<u>Lischner</u> does not teach or suggest a package substrate having a thermally conductive substrate core and a buildup layer being, having conductive traces and vias interconnecting top and bottom surface of the buildup layer, disposed only on a first portion of the substrate core and a heat spreader mounted to a second portion of a substrate core. <u>Lischner</u> teaches a circuit board assembly 100 with a flip chip

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806

package 110, having a heat spreader 140, connected to a printed circuit board 150 (Col. 2, lines 14-17). The first substrate 120 has a first surface 125 and a second surface 126 (Col. 2, lines 19-20). The substrate may have a plurality of levels, which could be called buildup layers, with electrical paths between layers provided by interconnect vias 122 (Col. 2, lines 23-25). As clearly shown in Figures 1 and 3, these layers completely cover the substrate 120. There is no portion of a substrate 120 that is left uncovered by the buildup layers. Furthermore, the heat spreader as clearly shown in Figures 1 and 3 is attached to the buildup layers, not the substrate 120. Thus, <u>Lischner</u> teaches buildup layers completely covering a substrate core and a heat spreader attached to the buildup layers. Specifically, Lischner does not teach or suggest a package substrate having a thermally conductive substrate core and a buildup layer being, having conductive traces and vias interconnecting top and bottom surface of the buildup layer, disposed only on a first portion of the substrate core and a heat spreader mounted to a second portion of a substrate core.

As previously discussed, <u>Hiyoshi</u> does not teach or suggest a package substrate having a thermally conductive substrate core and a buildup layer being, having conductive traces and vias interconnecting top and bottom surface of the buildup layer.

Therefore, claim 10 is patentable over <u>Lischner</u> in view of <u>Hiyoshi</u> because claim 10 includes a limitation that is not taught or suggested by <u>Lischner</u> and <u>Hiyoshi</u>.

Inventor(s): Timothy M. Takeuchi

Application No.: 10/038,806

- 12/18
Examiner: Vu, Quang D.

Art Unit: 2811

Claims 11-15 and 18-20 are dependent on claim 10 and should be allowable for the same reasons as claim 10.

Applicant, accordingly, respectfully requests withdrawal of the rejections of claims 10-15 and 18-20 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> in view of <u>Hiyoshi</u>.

The Examiner has rejected claims 16 and 17 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> in view of <u>Hiyoshi</u> and further in view of <u>Hembree</u>.

Claims 16 and 17 are dependent on claim 10 and should be allowable for the same reasons as claim 10.

Applicant, accordingly, respectfully requests withdrawal of the rejections of claims 16 and 17 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> in view of <u>Hiyoshi</u> and further in view of <u>Hembree</u>.

The Examiner has rejected claim 21 under 35 U.S.C. § 103(a) as being unpatentable over <u>Kohara</u> in view of <u>Hiyoshi</u>.

Claim 21 includes a package substrate having a thermally conductive substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core. Specifically, claim 21 includes the limitations "a package substrate including a thermally conductive substrate core, having first and

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806 second portions, and a buildup layer, including a plurality of conductive traces and vias formed therein interconnecting top and bottom surfaces of the buildup layer, being disposed on only the first portion of the substrate core" and "a heat spreader mounted to the second portion of the substrate core."

Kohara and Hiyoshi do not teach or suggest a package substrate having a thermally conductive substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core.

Kohara does not teach or suggest a package substrate having a thermally conductive substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core. Kohara teaches a semiconductor device including a flange 2 and flip-chips 6 mounted to a module base board 7. The flange 2 is also mounted to a heat sink 1 (Col. 5, lines 7-11). Kohara makes no mention of a package substrate with layers formed thereon. Specifically, Kohara does not teach or suggest a package substrate having a thermally conductive substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core.

Inventor(s): Timothy M. Takeuchi
Application No.: 10/038,806

- 14/18
Examiner: Vu, Quang D.

Art Unit: 2811

As previously discussed, <u>Hiyoshi</u> does not teach or suggest a package substrate having a thermally conductive substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer.

Therefore, claim 21 is patentable over <u>Kohara</u> in view of <u>Hiyoshi</u> because claim 21 includes limitations that are not taught or suggested by <u>Kohara</u> and <u>Hiyoshi</u>.

Applicant, accordingly, respectfully requests withdrawal of the rejection of claim 21 under 35 U.S.C. § 103(a) as being unpatentable over Kohara in view of Hiyoshi.

The Examiner has rejected claim 22 under 35 U.S.C. § 103(a) as being unpatentable over Kohara in view of Hiyoshi and further in view of Khandros.

Claim 22 is dependent on claim 21 and should be allowable for the same reasons as claim 21.

Applicant, accordingly, respectfully requests withdrawal of the rejection of claim 22 under 35 U.S.C. § 103(a) as being unpatentable over Kohara in view of Hiyoshi and further in view of Khandros.

The Examiner has rejected claim 23 under 35 U.S.C. § 103(a) as being unpatentable over Kohara in view of Hiyoshi and further in view of Lischner.

Inventor(s): Timothy M. Takeuchi

Application No.: 10/038,806

- 15/18
Examiner: Vu, Quang D.

Art Unit: 2811

Claim 23 is dependent on claim 21 and should be allowable for the same reasons as claim 21.

Applicant, accordingly, respectfully requests withdrawal of the rejection of claim 23 under 35 U.S.C. § 103(a) as being unpatentable over <u>Kohara</u> in view of <u>Hiyoshi</u> and further in view of <u>Lischner</u>.

The Examiner has rejected claims 24 and 25 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> in view of <u>Hiyoshi</u> and further in view of <u>Ommen</u>.

Claim 24 includes a package substrate having a metal substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core. Specifically, claim 24 includes the limitations "a package substrate including a metal substrate core, having first and second portions, and a buildup layer, having a plurality of conductive traces and vias formed therein interconnecting top and bottom surfaces of the buildup layer, disposed on the first portion of the substrate core" and "a heat spreader mounted to the second portion of the substrate core."

As previously discussed, <u>Lischner</u> does not teach or suggest a package substrate having a metal substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core.

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806

As previously discussed, <u>Hiyoshi</u> does not teach or suggest a package substrate having a metal substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core.

Also as previously discussed, <u>Ommen</u> does not teach or suggest a package substrate having a metal substrate core, a buildup layer, having a plurality of conductive traces and vias interconnecting top and bottom surfaces of the buildup layer, being disposed on only a first portion of the substrate core, and a heat spreader mounted to a second portion of the substrate core.

Therefore, claim 24 is patentable over <u>Lischner</u> in view of <u>Hiyoshi</u> and further in view of <u>Ommen</u> because claim 24 includes limitations that are not taught or suggested by <u>Lischner</u>, <u>Hiyoshi</u>, and <u>Ommen</u>.

Claim 25 is dependent on claim 24 and should be allowable for the same reasons as claim 24.

Applicant, accordingly, respectfully requests withdrawal of the rejections of claims 24 and 25 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> in view of <u>Hiyoshi</u> and further in view of <u>Ommen</u>.

The Examiner has rejected claim 26 under 35 U.S.C. § 103(a) as being unpatentable over <u>Lischner</u> and <u>Hiyoshi</u> in view of <u>Ommen</u> and further in view of <u>Hembree</u>.

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806 Examiner: Vu, Quang D.
Art Unit: 2811

Claim 26 is dependent on claim 24 and should be allowable for the same

reasons as claim 24.

Applicant, accordingly, respectfully requests withdrawal of the rejection of

claim 26 under 35 U.S.C. § 103(a) as being unpatentable over Lischner and Hiyoshi

in view of Ommen and further in view of Hembree.

Applicant respectfully submits that the present application is in condition for

allowance. If the Examiner believes a telephone conference would expedite or assist

in the allowance of the present application, the Examiner is invited to call Michael A.

Bernadicou at (408) 720-8300.

Pursuant to 37 C.F.R. 1.136(a)(3), applicant(s) hereby request and authorize

the U.S. Patent and Trademark Office to (1) treat any concurrent or future reply that

requires a petition for extension of time as incorporating a petition for extension of

time for the appropriate length of time and (2) charge all required fees, including

extension of time fees and fees under 37 C.F.R. 1.16 and 1.17, to Deposit Account

No. 02-2666.

Respectfully submitted,

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN LLP

Date: December 16, 2003

Michael A. Bernadicou

Reg. No. 35,934

12400 Wilshire Blvd., 7th Floor Los Angeles, CA 90025-1030 (408) 720-8300

Inventor(s): Timothy M. Takeuchi Application No.: 10/038,806

- 18/18-

Examiner: Vu, Quang D.

Art Unit: 2811